


MT Ferrule



Using an ultra high plastic molding technique with a long history, Hakusan Inc. has been producing and marketing a wide range of MT ferrule. Besides the standard Single mode and Multimode MT ferrule with several fiber channels, the premium low loss types are available.



Materials	Mode	Product name	Applied Polishing	Number of Hole	Insertion loss (dB)		
					≤0.35	≤0.5	≤0.7
Thermoplastic PPS	Single mode	4MT-R	Flat (Matching gel)	4			●
		8MT-R	Flat (Matching gel)	8			●
		8MT-PA-S	Angled PC	8			●
		8MT-PA-SLS	Angled PC	8	●		
		12MT-PA-S	Angled PC	12			●
		12MT-PA-SLS	Angled PC	12	●		
		24MT-PA-S	Angled PC	24			●
	Multi mode	2mini-MT-M	Flat PC	2		●	
		12MT-PF-M	Flat PC	12		●	
		12MT-PF-SLM	Flat PC	12	●		
		24MT-PF-M	Flat PC	24		●	
		24MT-PF-SLM	Flat PC	24	●		
		16MT-PF-M	Flat PC	16		●	
		32MT-PF-M	Flat PC	32		●	

- Hakusan's 4MT-R ferrule has been confirmed to meet requirements of NTT's Specification on intermateability and compatibility.
- Hakusan has been granted the license for Angled PC polished MT connectors from the patent holder, NTT.



<http://www.hakusan-mfg.co.jp>
 10-13, 1-chome, Minamiikebukuro, Toshima-ku
 Tokyo, 171-0022 Japan
 TEL+81(0)3 5951 1614, FAX+81(0)3 5951 1216

Contents of this brochure may be changed without notification.

No.HI0808-04.10 2017.1